

MICHELIN MULTIBIB

Load Capacity



Productivity



Comfort



■ Load capacity

- Great performance in the field and on the road
- High flotation tire designed to fit on a standard wheel

■ Productivity

- High traction capacity to save time and fuel
- Flexible casing provides lower compaction
- Capable of speeds of up to 40 mph

■ Comfort

- Excellent road handling
- Increased ride comfort for the driver

■ Flat, wide crown

- Footprint: +10%*
- Reduced slip
- Consistent, regular wear

■ Flexible casing

- Increased ride comfort

■ Deep tread

- Up to 72/32 deep



*Compared with a MICHELIN XM 108 tire

Sizes

320/65	R16 TL 107A8/104B		480/65	R24 TL 133D	540/65	R34 TL 145D
320/65	R16 TL 107D	NEW	540/65	R24 TL 140D	600/65	R34 TL 151D
320/65	R18 TL 109A8/106B		420/65	R28 TL 128A8/128B	540/65	R38 TL 147D
340/65	R18 TL 113A8/110B		440/65	R28 TL 131D	600/65	R38 TL 153D
420/65	R20 TL 125A8/125B		480/65	R28 TL 136D	650/65	R38 TL 157D
420/65	R24 TL 126A8/126B		540/65	R28 TL 142D	650/65	R42 TL 158D
440/65	R24 TL 128D		540/65	R30 TL 143D		

MICHELIN MULTIBIB

320/65 R16 107D TL MULTIBIB

MSPN: 39517

CAI: 494658

Load per tire (single)						Tire Technical Data				
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	Pressure	Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)
						Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	
			1,150 lbs	840 lbs	6 psi	11.8 in	32.6 in	14.5 in	96.5 in	W8 W8L, W9, W10L
			520 kgs	380 kgs	0.4 bar	300 mm	827 mm	368 mm	2,452 mm	
1,080 lbs	1,120 lbs	1,170 lbs	1,260 lbs	1,110 lbs	7 psi	Rolling Circumference Index 0				Tube MSPN 03500
490 kgs	510 kgs	530 kgs	570 kgs	505 kgs	0.5 bar					
1,180 lbs	1,220 lbs	1,280 lbs	1,370 lbs	1,390 lbs	9 psi	Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing
535 kgs	555 kgs	580 kgs	620 kgs	630 kgs	0.6 bar					
1,380 lbs	1,430 lbs	1,500 lbs	1,590 lbs	1,680 lbs	12 psi		31 kgs	86 liters	29 mm	408 mm
625 kgs	650 kgs	680 kgs	720 kgs	760 kgs	0.8 bar					
1,570 lbs	1,640 lbs	1,710 lbs	1,810 lbs	1,950 lbs	15 psi					
710 kgs	745 kgs	775 kgs	820 kgs	885 kgs	1.0 bar					
1,760 lbs	1,850 lbs	1,930 lbs	2,030 lbs	2,240 lbs	17 psi					
800 kgs	840 kgs	875 kgs	920 kgs	1,015 kgs	1.2 bar					
1,960 lbs	2,050 lbs	2,140 lbs	2,250 lbs	2,510 lbs	20 psi					
890 kgs	930 kgs	970 kgs	1,020 kgs	1,140 kgs	1.4 bar					
2,150 lbs	2,260 lbs	2,360 lbs	2,480 lbs	2,800 lbs	23 psi					
975 kgs	1,025 kgs	1,070 kgs	1,125 kgs	1,270 kgs	1.6 bar					
				3,080 lbs	26 psi					
				1,395 kgs	1.8 bar					
				3,220 lbs	28 psi					
				1,460 kgs	1.9 bar					

*All load values are for maximum indicated speeds at low torque.

*20 mph (30 km/h): high torque field work or max road speed.

*All load values for ground slopes up to 20% (above 20% consult Michelin)

440/65 R20 128D TL MULTIBIB

MSPN: 15810

CAI: 675464

Load per tire (single)							Tire Technical Data				
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Pressure	Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)
							Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	
			2,030 lbs	1,700 lbs	6 psi	17.4 in	42.8 in	18.7 in	127.4 in	W14L W13, W15L	
			920 kgs	770 kgs	0.4 bar	441 mm	1,088 mm	474 mm	3,236 mm		
2,150 lbs	2,260 lbs	2,360 lbs	2,470 lbs	3,060 lbs	2,070 lbs	9 psi	Rolling Circumference Index 0				Tube MSPN
975 kgs	1,025 kgs	1,070 kgs	1,120 kgs	1,390 kgs	940 kgs	0.6 bar					
2,500 lbs	2,570 lbs	2,740 lbs	2,880 lbs	3,460 lbs	2,410 lbs	12 psi	Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing
1,135 kgs	1,165 kgs	1,245 kgs	1,305 kgs	1,570 kgs	1,095 kgs	0.8 bar					
2,840 lbs	2,890 lbs	3,120 lbs	3,270 lbs	3,860 lbs	2,740 lbs	15 psi		65 kgs	209 liters	44 mm	580 mm
1,290 kgs	1,310 kgs	1,415 kgs	1,485 kgs	1,750 kgs	1,245 kgs	1.0 bar					
3,200 lbs	3,200 lbs	3,510 lbs	3,680 lbs	4,250 lbs	3,090 lbs	17 psi					
1,450 kgs	1,450 kgs	1,590 kgs	1,670 kgs	1,930 kgs	1,400 kgs	1.2 bar					
3,580 lbs	3,680 lbs	3,920 lbs	4,120 lbs	4,670 lbs	3,460 lbs	20 psi					
1,625 kgs	1,670 kgs	1,780 kgs	1,870 kgs	2,120 kgs	1,570 kgs	1.4 bar					
3,970 lbs	4,170 lbs	4,340 lbs	4,560 lbs	5,100 lbs	3,830 lbs	23 psi					
1,800 kgs	1,890 kgs	1,970 kgs	2,070 kgs	2,315 kgs	1,735 kgs	1.6 bar					
				5,530 lbs		26 psi					
				2,510 kgs		1.8 bar					
				5,740 lbs		28 psi					
				2,605 kgs		1.9 bar					
				5,950 lbs		29 psi					
				2,700 kgs		2.0 bar					

*All load values are for maximum indicated speeds at low torque.

*20 mph (30 km/h): high torque field work or max road speed.

*All load values for ground slopes up to 20% (above 20% consult Michelin)

NOTE:

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%





440/65 R24 128D TL MULTIBIB

MSPN: 04039

CAI: 426389

Load per tire (single)							*All load values are for maximum indicated speeds at low torque. *20 mph (30 km/h): high torque field work or max road speed. *All load values for ground slopes up to 20% (above 20% consult Michelin)									
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Pressure	Tire Technical Data									
			2,160 lbs 980 kgs	2,830 lbs 1,285 kgs	1,810 lbs 820 kgs	6 psi 0.4 bar	Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)					
							Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference						
2,270 lbs 1,030 kgs	2,380 lbs 1,080 kgs	2,490 lbs 1,130 kgs	2,600 lbs 1,180 kgs	3,200 lbs 1,450 kgs	2,190 lbs 995 kgs	9 psi 0.6 bar	17.3 in 439 mm	46.7 in 1,187 mm	20.8 in 529 mm	138.5 in 3,519 mm	DW14L W13, DW13, W14L, W15L, DW15L					
2,660 lbs 1,205 kgs	2,790 lbs 1,265 kgs	2,910 lbs 1,320 kgs	3,040 lbs 1,380 kgs	3,650 lbs 1,655 kgs	2,560 lbs 1,160 kgs	12 psi 0.8 bar	<table border="1"> <tr> <td>Rolling Circumference Index</td> </tr> <tr> <td>0</td> </tr> <tr> <td>Number of Lugs</td> </tr> <tr> <td>19 x 2</td> </tr> </table>				Rolling Circumference Index	0	Number of Lugs	19 x 2		
Rolling Circumference Index																
0																
Number of Lugs																
19 x 2																
3,030 lbs 1,375 kgs	3,190 lbs 1,445 kgs	3,330 lbs 1,510 kgs	3,480 lbs 1,580 kgs	4,090 lbs 1,855 kgs	2,930 lbs 1,330 kgs	15 psi 1.0 bar										
3,420 lbs 1,550 kgs	3,590 lbs 1,630 kgs	3,750 lbs 1,700 kgs	3,920 lbs 1,780 kgs	4,540 lbs 2,060 kgs	3,300 lbs 1,495 kgs	17 psi 1.2 bar					Tube MSPN 96691					
3,690 lbs 1,675 kgs	3,880 lbs 1,760 kgs	4,050 lbs 1,835 kgs	4,240 lbs 1,925 kgs	4,910 lbs 2,225 kgs	3,560 lbs 1,615 kgs	20 psi 1.4 bar					Tube CAI 171114					
3,970 lbs 1,800 kgs	4,170 lbs 1,890 kgs	4,340 lbs 1,970 kgs	4,560 lbs 2,070 kgs	5,270 lbs 2,390 kgs	3,830 lbs 1,735 kgs	23 psi 1.6 bar					Minimum Dual/Triple Spacing					
				5,640 lbs 2,560 kgs		26 psi 1.8 bar	Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	22.8 in					
				5,820 lbs 2,640 kgs		28 psi 1.9 bar	197 sq in 1,269 sq cm	164 lbs 75 kgs	62.6 gals 237 liters	55/32nd 44 mm	580 mm					
				6,010 lbs		29 psi 1.9 bar										

480/65 R24 133D TL MULTIBIB

MSPN: 03176

CAI: 531721

Load per tire (single)							*All load values are for maximum indicated speeds at low torque. *20 mph (30 km/h): high torque field work or max road speed. *All load values for ground slopes up to 20% (above 20% consult Michelin)									
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Pressure	Tire Technical Data									
			1,120 kgs	1,450 kgs	2,070 lbs 940 kgs	6 psi 0.4 bar	Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)					
							Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference						
2,600 lbs 1,180 kgs	2,730 lbs 1,240 kgs	2,840 lbs 1,290 kgs	3,000 lbs 1,360 kgs	3,750 lbs 1,700 kgs	2,500 lbs 1,135 kgs	9 psi 0.6 bar	19.0 in 483 mm	48.8 in 1,240 mm	21.5 in 546 mm	144.4 in 3,667 mm	DW15L DW14L, W15L					
3,020 lbs 1,370 kgs	3,170 lbs 1,440 kgs	3,310 lbs 1,500 kgs	3,470 lbs 1,575 kgs	4,230 lbs 1,920 kgs	2,910 lbs 1,320 kgs	12 psi 0.8 bar	<table border="1"> <tr> <td>Rolling Circumference Index</td> </tr> <tr> <td>38</td> </tr> <tr> <td>Number of Lugs</td> </tr> <tr> <td>19 x 2</td> </tr> </table>				Rolling Circumference Index	38	Number of Lugs	19 x 2		
Rolling Circumference Index																
38																
Number of Lugs																
19 x 2																
3,440 lbs 1,560 kgs	3,620 lbs 1,640 kgs	3,770 lbs 1,710 kgs	3,960 lbs 1,795 kgs	4,720 lbs 2,140 kgs	3,320 lbs 1,505 kgs	15 psi 1.0 bar					Tube MSPN 44140					
3,860 lbs 1,750 kgs	4,060 lbs 1,840 kgs	4,230 lbs 1,920 kgs	4,430 lbs 2,010 kgs	5,200 lbs 2,360 kgs	3,730 lbs 1,690 kgs	17 psi 1.2 bar					Tube CAI 170042					
4,200 lbs 1,905 kgs	4,410 lbs 2,000 kgs	4,610 lbs 2,090 kgs	4,830 lbs 2,190 kgs	5,640 lbs 2,560 kgs	4,060 lbs 1,840 kgs	20 psi 1.4 bar					Minimum Dual/Triple Spacing					
4,540 lbs 2,060 kgs	4,760 lbs 2,160 kgs	4,980 lbs 2,260 kgs	5,220 lbs 2,370 kgs	6,070 lbs 2,755 kgs	4,390 lbs 1,990 kgs	23 psi 1.6 bar	Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	24.6 in					
				6,500 lbs 2,950 kgs		26 psi 1.8 bar	218 sq in 1,407 sq cm	179 lbs 81 kgs	76.9 gals 291 liters	58/32nd 46 mm	626 mm					
				6,720 lbs 3,050 kgs		28 psi 1.9 bar										
				6,940 lbs 3,150 kgs		29 psi 2.0 bar										

NOTE:

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%



MICHELIN MULTIBIB

540/65 R24 140D TL MULTIBIB

MSPN: 08801

CAI: 097057

Load per tire (single)							Pressure	Tire Technical Data										
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)								
			3,000 lbs 1,360 kgs	3,860 lbs 1,750 kgs	2,510 lbs 1,140 kgs	6 psi 0.4 bar	Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	DW16L W16L, W18L, DW18L							
3,090 lbs 1,400 kgs	3,240 lbs 1,470 kgs	3,370 lbs 1,530 kgs	3,550 lbs 1,610 kgs	4,410 lbs 2,000 kgs	2,970 lbs 1,345 kgs	9 psi 0.6 bar	20.9 in 532 mm	51.7 in 1,312 mm	22.6 in 573 mm	152.5 in 3,873 mm								
3,620 lbs 1,640 kgs	3,800 lbs 1,725 kgs	3,960 lbs 1,795 kgs	4,160 lbs 1,885 kgs	4,990 lbs 2,265 kgs	3,470 lbs 1,575 kgs	12 psi 0.8 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">0</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">19 x 2</td> </tr> </table>					Rolling Circumference Index		0		Number of Lugs		19 x 2
Rolling Circumference Index																		
0																		
Number of Lugs																		
19 x 2																		
4,140 lbs 1,880 kgs	4,350 lbs 1,975 kgs	4,530 lbs 2,055 kgs	4,770 lbs 2,165 kgs	5,590 lbs 2,535 kgs	3,990 lbs 1,810 kgs	15 psi 1.0 bar	Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing							
4,670 lbs 2,120 kgs	4,920 lbs 2,230 kgs	5,110 lbs 2,320 kgs	5,380 lbs 2,440 kgs	6,170 lbs 2,800 kgs	4,500 lbs 2,040 kgs	17 psi 1.2 bar	273 sq in 1,761 sq cm	232 lbs 105 kgs	101.2 gals 383 liters	60/32nd 48 mm	27.0 in 686 mm							
5,090 lbs 2,310 kgs	5,360 lbs 2,430 kgs	5,580 lbs 2,530 kgs	5,860 lbs 2,660 kgs	6,700 lbs 3,040 kgs	4,910 lbs 2,225 kgs	20 psi 1.4 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">39</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">20 x 2</td> </tr> </table>				Rolling Circumference Index		39		Number of Lugs		20 x 2	
Rolling Circumference Index																		
39																		
Number of Lugs																		
20 x 2																		
5,510 lbs 2,500 kgs	5,800 lbs 2,630 kgs	6,040 lbs 2,740 kgs	6,350 lbs 2,880 kgs	7,220 lbs 3,275 kgs	5,310 lbs 2,410 kgs	23 psi 1.6 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">0</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">19 x 2</td> </tr> </table>				Rolling Circumference Index		0		Number of Lugs		19 x 2	
Rolling Circumference Index																		
0																		
Number of Lugs																		
19 x 2																		
				7,740 lbs 3,510 kgs		26 psi 1.8 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">39</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">20 x 2</td> </tr> </table>				Rolling Circumference Index		39		Number of Lugs		20 x 2	
Rolling Circumference Index																		
39																		
Number of Lugs																		
20 x 2																		
				8,000 lbs 3,630 kgs		28 psi 1.9 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">0</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">19 x 2</td> </tr> </table>				Rolling Circumference Index		0		Number of Lugs		19 x 2	
Rolling Circumference Index																		
0																		
Number of Lugs																		
19 x 2																		
				8,270 lbs 3,750 kgs		29 psi 2.0 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">0</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">19 x 2</td> </tr> </table>				Rolling Circumference Index		0		Number of Lugs		19 x 2	
Rolling Circumference Index																		
0																		
Number of Lugs																		
19 x 2																		
							<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">0</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">19 x 2</td> </tr> </table>				Rolling Circumference Index		0		Number of Lugs		19 x 2	
Rolling Circumference Index																		
0																		
Number of Lugs																		
19 x 2																		

*All load values are for maximum indicated speeds at low torque.

*20 mph (30 km/h): high torque field work or max road speed.

*All load values for ground slopes up to 20% (above 20% consult Michelin)

440/65 R28 131D TL MULTIBIB

MSPN: 96372

CAI: 386212

Load per tire (single)							Pressure	Tire Technical Data										
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)								
			2,340 lbs 1,060 kgs	3,000 lbs 1,360 kgs	1,960 lbs 890 kgs	6 psi 0.4 bar	Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	DW14L W13, W14L, W15L, DW15L							
2,400 lbs 1,090 kgs	2,510 lbs 1,140 kgs	2,620 lbs 1,190 kgs	2,760 lbs 1,250 kgs	3,530 lbs 1,600 kgs	2,300 lbs 1,045 kgs	9 psi 0.6 bar	17.2 in 437 mm	50.8 in 1,291 mm	22.8 in 579 mm	150.9 in 3,833 mm								
2,810 lbs 1,275 kgs	2,940 lbs 1,335 kgs	3,080 lbs 1,395 kgs	3,230 lbs 1,465 kgs	3,960 lbs 1,795 kgs	2,710 lbs 1,230 kgs	12 psi 0.8 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">39</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">20 x 2</td> </tr> </table>					Rolling Circumference Index		39		Number of Lugs		20 x 2
Rolling Circumference Index																		
39																		
Number of Lugs																		
20 x 2																		
3,230 lbs 1,465 kgs	3,380 lbs 1,535 kgs	3,540 lbs 1,605 kgs	3,710 lbs 1,685 kgs	4,380 lbs 1,985 kgs	3,110 lbs 1,410 kgs	15 psi 1.0 bar	Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing							
3,640 lbs 1,650 kgs	3,810 lbs 1,730 kgs	3,990 lbs 1,810 kgs	4,190 lbs 1,900 kgs	4,810 lbs 2,180 kgs	3,520 lbs 1,595 kgs	17 psi 1.2 bar	220 sq in 1,421 sq cm	182 lbs 82 kgs	69.7 gals 264 liters	54/32nd 43 mm	22.8 in 580 mm							
3,970 lbs 1,800 kgs	4,170 lbs 1,890 kgs	4,350 lbs 1,975 kgs	4,560 lbs 2,070 kgs	5,200 lbs 2,360 kgs	3,840 lbs 1,740 kgs	20 psi 1.4 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">39</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">20 x 2</td> </tr> </table>				Rolling Circumference Index		39		Number of Lugs		20 x 2	
Rolling Circumference Index																		
39																		
Number of Lugs																		
20 x 2																		
4,300 lbs 1,950 kgs	4,520 lbs 2,050 kgs	4,720 lbs 2,140 kgs	4,940 lbs 2,240 kgs	5,600 lbs 2,540 kgs	4,160 lbs 1,885 kgs	23 psi 1.6 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">39</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">20 x 2</td> </tr> </table>				Rolling Circumference Index		39		Number of Lugs		20 x 2	
Rolling Circumference Index																		
39																		
Number of Lugs																		
20 x 2																		
				6,000 lbs 2,720 kgs		26 psi 1.8 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">39</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">20 x 2</td> </tr> </table>				Rolling Circumference Index		39		Number of Lugs		20 x 2	
Rolling Circumference Index																		
39																		
Number of Lugs																		
20 x 2																		
				6,190 lbs 2,810 kgs		28 psi 1.9 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">39</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">20 x 2</td> </tr> </table>				Rolling Circumference Index		39		Number of Lugs		20 x 2	
Rolling Circumference Index																		
39																		
Number of Lugs																		
20 x 2																		
				6,390 lbs 2,900 kgs		29 psi 2.0 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">39</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">20 x 2</td> </tr> </table>				Rolling Circumference Index		39		Number of Lugs		20 x 2	
Rolling Circumference Index																		
39																		
Number of Lugs																		
20 x 2																		

*All load values are for maximum indicated speeds at low torque.

*20 mph (30 km/h): high torque field work or max road speed.

*All load values for ground slopes up to 20% (above 20% consult Michelin)

NOTE:

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%





480/65 R28 136D TL MULTIBIB

MSPN: 14369

CAI: 897574

Load per tire (single)						
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Pressure
			2,600 lbs 1,180 kgs	3,420 lbs 1,550 kgs	2,180 lbs 990 kgs	6 psi 0.4 bar
2,760 lbs 1,250 kgs	2,890 lbs 1,310 kgs	3,020 lbs 1,370 kgs	3,170 lbs 1,440 kgs	3,970 lbs 1,800 kgs	2,660 lbs 1,205 kgs	9 psi 0.6 bar
3,230 lbs 1,465 kgs	3,400 lbs 1,540 kgs	3,540 lbs 1,605 kgs	3,730 lbs 1,690 kgs	4,490 lbs 2,035 kgs	3,120 lbs 1,415 kgs	12 psi 0.8 bar
3,710 lbs 1,685 kgs	3,900 lbs 1,770 kgs	4,070 lbs 1,845 kgs	4,280 lbs 1,940 kgs	4,990 lbs 2,265 kgs	3,570 lbs 1,620 kgs	15 psi 1.0 bar
4,190 lbs 1,900 kgs	4,410 lbs 2,000 kgs	4,590 lbs 2,080 kgs	4,830 lbs 2,190 kgs	5,510 lbs 2,500 kgs	4,030 lbs 1,830 kgs	17 psi 1.2 bar
4,560 lbs 2,070 kgs	4,800 lbs 2,175 kgs	4,990 lbs 2,265 kgs	5,260 lbs 2,385 kgs	5,970 lbs 2,710 kgs	4,390 lbs 1,990 kgs	20 psi 1.4 bar
4,940 lbs 2,240 kgs	5,180 lbs 2,350 kgs	5,400 lbs 2,450 kgs	5,690 lbs 2,580 kgs	6,450 lbs 2,925 kgs	4,750 lbs 2,155 kgs	23 psi 1.6 bar
				6,920 lbs 3,140 kgs		26 psi 1.8 bar
				7,150 lbs 3,245 kgs		28 psi 1.9 bar
				7,390 lbs 3,350 kgs		29 psi 2.0 bar

*All load values are for maximum indicated speeds at low torque.
***20 mph (30 km/h): high torque field work or max road speed.**
 *All load values for ground slopes up to 20% (above 20% consult Michelin)

Tire Technical Data

Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)
Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	
18.7 in 476 mm	52.7 in 1,339 mm	23.5 in 596 mm	156.3 in 3,970 mm	DW15L W14L, DW14L, W15L
Rolling Circumference Index				Tube MSPN 76858
0				
Number of Lugs				Tube CAI 170149
19 x 2				
Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing
244 sq in 1,577 sq cm	198 lbs 90 kgs	85.0 gals 322 liters	57/32nd 45 mm	24.6 in 626 mm

540/65 R28 142D TL MULTIBIB

MSPN: 36062

CAI: 792274

Load per tire (single)						
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Pressure
			3,170 lbs 1,440 kgs	4,190 lbs 1,900 kgs	2,660 lbs 1,205 kgs	6 psi 0.4 bar
3,310 lbs 1,500 kgs	3,480 lbs 1,580 kgs	3,620 lbs 1,640 kgs	3,810 lbs 1,730 kgs	4,810 lbs 2,180 kgs	3,190 lbs 1,445 kgs	9 psi 0.6 bar
3,850 lbs 1,745 kgs	4,050 lbs 1,835 kgs	4,210 lbs 1,910 kgs	4,440 lbs 2,015 kgs	5,410 lbs 2,455 kgs	3,700 lbs 1,680 kgs	12 psi 0.8 bar
4,400 lbs 1,995 kgs	4,620 lbs 2,095 kgs	4,810 lbs 2,180 kgs	5,060 lbs 2,295 kgs	6,010 lbs 2,725 kgs	4,230 lbs 1,920 kgs	15 psi 1.0 bar
4,940 lbs 2,240 kgs	5,180 lbs 2,350 kgs	5,400 lbs 2,450 kgs	5,690 lbs 2,580 kgs	6,610 lbs 3,000 kgs	4,750 lbs 2,155 kgs	17 psi 1.2 bar
5,390 lbs 2,445 kgs	5,650 lbs 2,565 kgs	5,900 lbs 2,675 kgs	6,210 lbs 2,815 kgs	7,170 lbs 3,250 kgs	5,180 lbs 2,350 kgs	20 psi 1.4 bar
5,840 lbs 2,650 kgs	6,130 lbs 2,780 kgs	6,390 lbs 2,900 kgs	6,720 lbs 3,050 kgs	7,720 lbs 3,500 kgs	5,620 lbs 2,550 kgs	23 psi 1.6 bar
				8,270 lbs 3,750 kgs		26 psi 1.8 bar
				8,540 lbs 3,875 kgs		28 psi 1.9 bar
				8,820 lbs 4,000 kgs		29 psi 2.0 bar

*All load values are for maximum indicated speeds at low torque.
***20 mph (30 km/h): high torque field work or max road speed.**
 *All load values for ground slopes up to 20% (above 20% consult Michelin)

Tire Technical Data

Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)
Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	
20.8 in 529 mm	56.2 in 1,427 mm	24.8 in 630 mm	166.3 in 4,223 mm	DW16L W16L, W18L, DW18L
Rolling Circumference Index				Tube MSPN 76858
41				
Number of Lugs				Tube CAI 170149
20 x 2				
Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing
278 sq in 1,796 sq cm	252 lbs 114 kgs	112.0 gals 424 liters	60/32nd 48 mm	27.0 in 686 mm

NOTE:

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%



MICHELIN MULTIBIB

540/65 R30 143D TL MULTIBIB

MSPN: 28553

CAI: 223153

Load per tire (single)							Pressure	Tire Technical Data			
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)	
			3,260 lbs 1,480 kgs	4,300 lbs 1,950 kgs	2,730 lbs 1,240 kgs	6 psi 0.4 bar	Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	DW16L W16L, W18L, DW18L
3,420 lbs 1,550 kgs	3,590 lbs 1,630 kgs	3,750 lbs 1,700 kgs	3,920 lbs 1,780 kgs	4,940 lbs 2,240 kgs	3,300 lbs 1,495 kgs	9 psi 0.6 bar	20.7 in 527 mm	58.0 in 1,472 mm	25.5 in 648 mm	171.4 in 4,353 mm	
3,970 lbs 1,800 kgs	4,180 lbs 1,895 kgs	4,350 lbs 1,975 kgs	4,560 lbs 2,070 kgs	5,560 lbs 2,520 kgs	3,830 lbs 1,735 kgs	12 psi 0.8 bar	Rolling Circumference Index 0 Number of Lugs 20 x 2				
4,520 lbs 2,050 kgs	4,750 lbs 2,155 kgs	4,950 lbs 2,245 kgs	5,200 lbs 2,360 kgs	6,160 lbs 2,795 kgs	4,370 lbs 1,980 kgs	15 psi 1.0 bar					Gross Flat Plate
5,070 lbs 2,300 kgs	5,340 lbs 2,420 kgs	5,560 lbs 2,520 kgs	5,840 lbs 2,650 kgs	6,780 lbs 3,075 kgs	4,890 lbs 2,220 kgs	17 psi 1.2 bar	1,981 sq cm	285 lbs 129 kgs	117.3 gals 444 liters	60/32nd 48 mm	27.0 in 686 mm
5,530 lbs 2,510 kgs	5,820 lbs 2,640 kgs	6,060 lbs 2,750 kgs	6,370 lbs 2,890 kgs	7,360 lbs 3,340 kgs	5,340 lbs 2,420 kgs	20 psi 1.4 bar					
6,010 lbs 2,725 kgs	6,310 lbs 2,860 kgs	6,570 lbs 2,980 kgs	6,900 lbs 3,130 kgs	7,940 lbs 3,600 kgs	5,780 lbs 2,620 kgs	23 psi 1.6 bar					
				8,510 lbs 3,860 kgs		26 psi 1.8 bar					
				8,810 lbs 3,995 kgs		28 psi 1.9 bar					
				9,090 lbs 4,125 kgs		29 psi 2.0 bar					

*All load values are for maximum indicated speeds at low torque.

*20 mph (30 km/h): high torque field work or max road speed.

*All load values for ground slopes up to 20% (above 20% consult Michelin)

540/65 R34 145D TL MULTIBIB

MSPN: 22243

CAI: 712064

Load per tire (single)							Pressure	Tire Technical Data			
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)	
			3,440 lbs 1,560 kgs	4,540 lbs 2,060 kgs	2,890 lbs 1,310 kgs	6 psi 0.4 bar	Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	DW16L DW18L, W16L, W18L
3,640 lbs 1,650 kgs	3,810 lbs 1,730 kgs	3,990 lbs 1,810 kgs	4,190 lbs 1,900 kgs	5,200 lbs 2,360 kgs	3,520 lbs 1,595 kgs	9 psi 0.6 bar	20.9 in 530 mm	62.0 in 1,574 mm	27.3 in 693 mm	183.3 in 4,655 mm	
4,270 lbs 1,935 kgs	4,480 lbs 2,030 kgs	4,670 lbs 2,120 kgs	4,910 lbs 2,225 kgs	5,850 lbs 2,655 kgs	4,110 lbs 1,865 kgs	12 psi 0.8 bar	Rolling Circumference Index 43 Number of Lugs 21 x 2				
4,880 lbs 2,215 kgs	5,140 lbs 2,330 kgs	5,360 lbs 2,430 kgs	5,630 lbs 2,555 kgs	6,510 lbs 2,955 kgs	4,720 lbs 2,140 kgs	15 psi 1.0 bar					Gross Flat Plate
5,510 lbs 2,500 kgs	5,800 lbs 2,630 kgs	6,040 lbs 2,740 kgs	6,350 lbs 2,880 kgs	7,170 lbs 3,250 kgs	5,310 lbs 2,410 kgs	17 psi 1.2 bar	2,044 sq cm	290 lbs 132 kgs	128.1 gals 485 liters	60/32nd 48 mm	27.0 in 686 mm
5,950 lbs 2,700 kgs	6,260 lbs 2,840 kgs	6,530 lbs 2,960 kgs	6,860 lbs 3,110 kgs	7,780 lbs 3,530 kgs	5,740 lbs 2,605 kgs	20 psi 1.4 bar					
6,390 lbs 2,900 kgs	6,720 lbs 3,050 kgs	7,010 lbs 3,180 kgs	7,360 lbs 3,340 kgs	8,400 lbs 3,810 kgs	6,170 lbs 2,800 kgs	23 psi 1.6 bar					
				9,030 lbs 4,095 kgs		26 psi 1.8 bar					
				9,340 lbs 4,235 kgs		28 psi 1.9 bar					
				9,650 lbs 4,375 kgs		29 psi 2.0 bar					

*All load values are for maximum indicated speeds at low torque.

*20 mph (30 km/h): high torque field work or max road speed.

*All load values for ground slopes up to 20% (above 20% consult Michelin)

NOTE:

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%





600/65 R34 151D TL MULTIBIB

MSPN: 16291

CAI: 557189

Load per tire (single)							*All load values are for maximum indicated speeds at low torque. *20 mph (30 km/h): high torque field work or max road speed. *All load values for ground slopes up to 20% (above 20% consult Michelin)				
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Pressure	Tire Technical Data				Rims (preferred in bold)
Unloaded Dimensions		Loaded Dimensions		Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	Rims (preferred in bold)			
			4,060 lbs 1,840 kgs					5,360 lbs 2,430 kgs	3,400 lbs 1,540 kgs	6 psi 0.4 bar	23.4 in 594 mm
4,300 lbs 1,950 kgs	4,520 lbs 2,050 kgs	4,720 lbs 2,140 kgs	4,940 lbs 2,240 kgs	6,170 lbs 2,800 kgs	4,160 lbs 1,885 kgs	9 psi 0.6 bar	Rolling Circumference Index 44				Tube MSPN 71039
4,990 lbs 2,265 kgs	5,260 lbs 2,385 kgs	5,480 lbs 2,485 kgs	5,740 lbs 2,605 kgs	6,970 lbs 3,160 kgs	4,830 lbs 2,190 kgs	12 psi 0.8 bar					Number of Lugs 20 x 2
5,700 lbs 2,585 kgs	5,990 lbs 2,715 kgs	6,250 lbs 2,835 kgs	6,560 lbs 2,975 kgs	7,750 lbs 3,515 kgs	5,500 lbs 2,495 kgs	15 psi 1.0 bar	Gross Flat Plate				
6,390 lbs 2,900 kgs	6,720 lbs 3,050 kgs	7,010 lbs 3,180 kgs	7,360 lbs 3,340 kgs	8,540 lbs 3,875 kgs	6,170 lbs 2,800 kgs	17 psi 1.2 bar					Tire Weight
7,000 lbs 3,175 kgs	7,350 lbs 3,335 kgs	7,670 lbs 3,480 kgs	8,060 lbs 3,655 kgs	9,250 lbs 4,195 kgs	6,750 lbs 3,060 kgs	20 psi 1.4 bar	383 sq in 2,472 sq cm	373 lbs 169 kgs	163.2 gals 618 liters	68/32nd 54 mm	760 mm
7,610 lbs 3,450 kgs	7,980 lbs 3,620 kgs	8,330 lbs 3,780 kgs	8,750 lbs 3,970 kgs	9,940 lbs 4,510 kgs	7,330 lbs 3,325 kgs	23 psi 1.6 bar	Gross Flat Plate				Minimum Dual/Triple Spacing
				10,650 lbs 4,830 kgs		26 psi 1.8 bar					
				11,000 lbs 4,990 kgs		28 psi 1.9 bar	Gross Flat Plate				Minimum Dual/Triple Spacing
				11,350 lbs 5,150 kgs		29 psi 2.0 bar					

540/65 R38 147D TL MULTIBIB

MSPN: 28857

CAI: 114518

Load per tire (single)							*All load values are for maximum indicated speeds at low torque. *20 mph (30 km/h): high torque field work or max road speed. *All load values for ground slopes up to 20% (above 20% consult Michelin)				
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Pressure	Tire Technical Data				Rims (preferred in bold)
Unloaded Dimensions		Loaded Dimensions		Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	Rims (preferred in bold)			
			3,680 lbs 1,670 kgs					4,810 lbs 2,180 kgs	3,090 lbs 1,400 kgs	6 psi 0.4 bar	20.8 in 529 mm
3,860 lbs 1,750 kgs	4,060 lbs 1,840 kgs	4,230 lbs 1,920 kgs	4,430 lbs 2,010 kgs	5,510 lbs 2,500 kgs	3,730 lbs 1,690 kgs	9 psi 0.6 bar	Rolling Circumference Index 44				Tube MSPN 67917
4,460 lbs 2,025 kgs	4,680 lbs 2,125 kgs	4,890 lbs 2,220 kgs	5,130 lbs 2,325 kgs	6,210 lbs 2,815 kgs	4,310 lbs 1,955 kgs	12 psi 0.8 bar					Number of Lugs 21 x 2
5,070 lbs 2,300 kgs	5,320 lbs 2,415 kgs	5,560 lbs 2,520 kgs	5,830 lbs 2,645 kgs	6,910 lbs 3,135 kgs	4,880 lbs 2,215 kgs	15 psi 1.0 bar	Gross Flat Plate				
5,680 lbs 2,575 kgs	5,950 lbs 2,700 kgs	6,220 lbs 2,820 kgs	6,530 lbs 2,960 kgs	7,610 lbs 3,450 kgs	5,470 lbs 2,480 kgs	17 psi 1.2 bar					Tire Weight
6,230 lbs 2,825 kgs	6,540 lbs 2,965 kgs	6,820 lbs 3,095 kgs	7,170 lbs 3,250 kgs	8,260 lbs 3,745 kgs	6,000 lbs 2,720 kgs	20 psi 1.4 bar	348 sq in 2,242 sq cm	324 lbs 147 kgs	138.7 gals 525 liters	60/32nd 48 mm	686 mm
6,780 lbs 3,075 kgs	7,120 lbs 3,230 kgs	7,430 lbs 3,370 kgs	7,800 lbs 3,540 kgs	8,910 lbs 4,040 kgs	6,540 lbs 2,965 kgs	23 psi 1.6 bar	Gross Flat Plate				Minimum Dual/Triple Spacing
				9,550 lbs 4,330 kgs		26 psi 1.8 bar					
				9,880 lbs 4,480 kgs		28 psi 1.9 bar	Gross Flat Plate				Minimum Dual/Triple Spacing
				10,200 lbs 4,625 kgs		29 psi 2.0 bar					

NOTE:

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%



MICHELIN MULTIBIB

600/65 R38 153D TL MULTIBIB

MSPN: 29767

CAI: 228045

Load per tire (single)							Pressure	Tire Technical Data											
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)									
			4,320 lbs 1,960 kgs	5,680 lbs 2,575 kgs	3,630 lbs 1,645 kgs	6 psi 0.4 bar	Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	DW20B (A) W18L, DW18L								
4,540 lbs 2,060 kgs	4,760 lbs 2,160 kgs	4,980 lbs 2,260 kgs	5,220 lbs 2,370 kgs	6,550 lbs 2,970 kgs	4,390 lbs 1,990 kgs	9 psi 0.6 bar	23.4 in 595 mm	69.6 in 1,768 mm	30.7 in 779 mm	205.9 in 5,229 mm									
5,290 lbs 2,400 kgs	5,540 lbs 2,515 kgs	5,800 lbs 2,630 kgs	6,080 lbs 2,760 kgs	7,400 lbs 3,355 kgs	5,100 lbs 2,315 kgs	12 psi 0.8 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">45</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">20 x 2</td> </tr> </table>				Rolling Circumference Index		45		Number of Lugs		20 x 2		Tube MSPN 80303
Rolling Circumference Index																			
45																			
Number of Lugs																			
20 x 2																			
6,030 lbs 2,735 kgs	6,340 lbs 2,875 kgs	6,610 lbs 3,000 kgs	6,940 lbs 3,150 kgs	8,250 lbs 3,740 kgs	5,820 lbs 2,640 kgs	15 psi 1.0 bar	Minimum Dual/Triple Spacing												
6,780 lbs 3,075 kgs	7,120 lbs 3,230 kgs	7,430 lbs 3,370 kgs	7,800 lbs 3,540 kgs	9,090 lbs 4,125 kgs	6,540 lbs 2,965 kgs	17 psi 1.2 bar	Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	29.9 in 760 mm								
7,410 lbs 3,360 kgs	7,780 lbs 3,530 kgs	8,120 lbs 3,685 kgs	8,530 lbs 3,870 kgs	9,820 lbs 4,455 kgs	7,140 lbs 3,240 kgs	20 psi 1.4 bar	417 sq in 2,689 sq cm	403 lbs 183 kgs	176.2 gals 667 liters	67/32nd 53 mm									
8,050 lbs 3,650 kgs	8,440 lbs 3,830 kgs	8,820 lbs 4,000 kgs	9,260 lbs 4,200 kgs	10,560 lbs 4,790 kgs	7,760 lbs 3,520 kgs	23 psi 1.6 bar													
				11,290 lbs 5,120 kgs		26 psi 1.8 bar													
				11,650 lbs 5,285 kgs		28 psi 1.9 bar													
				12,020 lbs 5,450 kgs		29 psi 2.0 bar													

*All load values are for maximum indicated speeds at low torque.

*20 mph (30 km/h): high torque field work or max road speed.

*All load values for ground slopes up to 20% (above 20% consult Michelin)

650/65 R38 157D TL MULTIBIB

MSPN: 12871

CAI: 292904

Load per tire (single)							Pressure	Tire Technical Data											
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)									
			4,830 lbs 2,190 kgs	6,390 lbs 2,900 kgs	4,050 lbs 1,835 kgs	6 psi 0.4 bar	Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	DW20B (A)								
5,070 lbs 2,300 kgs	5,340 lbs 2,420 kgs	5,560 lbs 2,520 kgs	5,840 lbs 2,650 kgs	7,390 lbs 3,350 kgs	4,890 lbs 2,220 kgs	9 psi 0.6 bar	25.4 in 646 mm	71.6 in 1,819 mm	31.6 in 801 mm	211.8 in 5,380 mm									
5,920 lbs 2,685 kgs	6,220 lbs 2,820 kgs	6,480 lbs 2,940 kgs	6,810 lbs 3,090 kgs	8,320 lbs 3,775 kgs	5,710 lbs 2,590 kgs	12 psi 0.8 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">46</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">20 x 2</td> </tr> </table>				Rolling Circumference Index		46		Number of Lugs		20 x 2		Tube MSPN 80303
Rolling Circumference Index																			
46																			
Number of Lugs																			
20 x 2																			
6,760 lbs 3,065 kgs	7,100 lbs 3,220 kgs	7,410 lbs 3,360 kgs	7,780 lbs 3,530 kgs	9,260 lbs 4,200 kgs	6,510 lbs 2,955 kgs	15 psi 1.0 bar	Minimum Dual/Triple Spacing												
7,610 lbs 3,450 kgs	7,980 lbs 3,620 kgs	8,330 lbs 3,780 kgs	8,750 lbs 3,970 kgs	10,200 lbs 4,625 kgs	7,330 lbs 3,325 kgs	17 psi 1.2 bar	Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	32.5 in 825 mm								
8,360 lbs 3,790 kgs	8,760 lbs 3,975 kgs	9,150 lbs 4,150 kgs	9,600 lbs 4,355 kgs	11,030 lbs 5,005 kgs	8,050 lbs 3,650 kgs	20 psi 1.4 bar	453 sq in 2,923 sq cm	451 lbs 205 kgs	212.1 gals 803 liters	71/32nd 56 mm									
9,090 lbs 4,125 kgs	9,550 lbs 4,330 kgs	9,960 lbs 4,520 kgs	10,450 lbs 4,740 kgs	11,880 lbs 5,390 kgs	8,770 lbs 3,980 kgs	23 psi 1.6 bar													
				12,720 lbs 5,770 kgs		26 psi 1.8 bar													
				13,140 lbs 5,960 kgs		28 psi 1.9 bar													
				13,560 lbs 6,150 kgs		29 psi 2.0 bar													

*All load values are for maximum indicated speeds at low torque.

*20 mph (30 km/h): high torque field work or max road speed.

*All load values for ground slopes up to 20% (above 20% consult Michelin)

NOTE:

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%





650/65 R42 158D TL MULTIBIB

MSPN: 38881

CAI: 167733

Load per tire (single)							Pressure	Tire Technical Data				Rims (preferred in bold)
40 mph 65 km/h	30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	6 psi 0.4 bar						
			5,070 lbs 2,300 kgs	6,610 lbs 3,000 kgs	4,250 lbs 1,930 kgs	6 psi 0.4 bar	Unloaded Dimensions Overall Width: 25.1 in / 638 mm Overall Diameter: 76.0 in / 1,931 mm Loaded Dimensions Loaded Radius: 33.8 in / 858 mm Rolling Circumference: 225.3 in / 5,722 mm				DW20B (A)	
5,360 lbs 2,430 kgs	5,620 lbs 2,550 kgs	5,860 lbs 2,660 kgs	6,150 lbs 2,790 kgs	7,610 lbs 3,450 kgs	5,160 lbs 2,340 kgs	9 psi 0.6 bar						
6,250 lbs 2,835 kgs	6,560 lbs 2,975 kgs	6,850 lbs 3,105 kgs	7,190 lbs 3,260 kgs	8,560 lbs 3,885 kgs	6,030 lbs 2,735 kgs	12 psi 0.8 bar	Rolling Circumference Index 47 Number of Lugs 21 x 2				Tube MSPN 75465	
7,150 lbs 3,245 kgs	7,510 lbs 3,405 kgs	7,840 lbs 3,555 kgs	8,220 lbs 3,730 kgs	9,510 lbs 4,315 kgs	6,890 lbs 3,125 kgs	15 psi 1.0 bar						
8,050 lbs 3,650 kgs	8,440 lbs 3,830 kgs	8,820 lbs 4,000 kgs	9,260 lbs 4,200 kgs	10,470 lbs 4,750 kgs	7,760 lbs 3,520 kgs	17 psi 1.2 bar	Gross Flat Plate 458 sq in / 2,952 sq cm Tire Weight 491 lbs / 223 kgs 100% Tire Volume 227.7 gals / 862 liters Centerline Tread Depth 72/32nd / 57 mm				Minimum Dual/Triple Spacing 32.5 in / 825 mm	
8,710 lbs 3,950 kgs	9,140 lbs 4,145 kgs	9,530 lbs 4,325 kgs	10,020 lbs 4,545 kgs	11,360 lbs 5,155 kgs	8,390 lbs 3,805 kgs	20 psi 1.4 bar						
9,370 lbs 4,250 kgs	9,830 lbs 4,460 kgs	10,250 lbs 4,650 kgs	10,780 lbs 4,890 kgs	12,260 lbs 5,560 kgs	9,020 lbs 4,090 kgs	23 psi 1.6 bar	Gross Flat Plate 458 sq in / 2,952 sq cm Tire Weight 491 lbs / 223 kgs 100% Tire Volume 227.7 gals / 862 liters Centerline Tread Depth 72/32nd / 57 mm				Minimum Dual/Triple Spacing 32.5 in / 825 mm	
				13,160 lbs 5,970 kgs		26 psi 1.8 bar						
				13,600 lbs 6,170 kgs		28 psi 1.9 bar	Gross Flat Plate 458 sq in / 2,952 sq cm Tire Weight 491 lbs / 223 kgs 100% Tire Volume 227.7 gals / 862 liters Centerline Tread Depth 72/32nd / 57 mm				Minimum Dual/Triple Spacing 32.5 in / 825 mm	
				14,050 lbs 6,375 kgs		29 psi 2.0 bar						

*All load values are for maximum indicated speeds at low torque.

***20 mph (30 km/h): high torque field work or max road speed.**

*All load values for ground slopes up to 20% (above 20% consult Michelin)

NOTE:

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%

