

TRACTOR RADIAL

R1W 80/85/95 | Standard Tyres 80/85/95 Series | Pattern R1W



- guaranteed true running and driving comfort up to 50 km/h
- wide contact area for up to 4000 working hours
- more and wider lugs in ground and extended wear compound for durability
- excellent driving on and off-the-road
- good self-cleaning abilities due to special angle lugs
- round shoulders for superior ground protection



TRACTOR RADIAL

R1 Genesis 85 | Genesis Tyres 85 Series | Pattern R1



- modern agricultural radial tyre
- the shape and angle of the lugs provide good traction and low slippage with excellent power transmission to the ground
- wide footprint area for improved stability and minimum ground pressure
- superior self-cleaning features that allow for a quick change from field operations to road usage
- low wear compound for longer tyre life



TRACTOR RADIAL

R1W 80/85/95 | R1 Genesis 85

tyre size	version	TT/TL	load/speed index	pattern	measured rim width	unloaded		static loaded radius	rolling circumference	inflation pressure	load		tread depth	
						outer diameter	section width				50 km/h	65 km/h		
						inch	mm				mm	mm±2.5%		mm±2.5%
210/95 R16	(7.50R16)		TL	106A8/106B	R1W	7	795	215	368	2373	240	950	-	32
210/95 R18	(7.50R18)		TL	108A8/108B	R1W	7	849	215	393	2542	240	1000	-	32
210/95R20	(8.30R20)		TL	110A8/110B	R1W	7	895	215	413	2686	240	1060	-	32
280/85 R20	(11.2R20)		TL	112A8/112B	R1W	10	986	282	446	2943	160	1120	-	41
280/85 R24	(11.2R24)		TL	115A8/115B	R1W	10	1080	285	494	3239	160	1215	-	41
320/85 R24	(12.4R24)		TL	122A8/122B	R1W	11	1139	322	520	3400	160	1500	-	43
340/85 R24	(13.6R24)		TL	125A8/125B	R1W	12	1191	353	547	3558	160	1650	-	45
380/85 R24	(14.9R24)		TL	131A8/131B	R1W	12	1273	382	566	3794	160	1950	-	47
420/85 R24	(16.9R24)		TL	137A8/137B	R1W	15	1322	439	593	3935	160	2300	-	48
280/85 R28	(11.2R28)		TL	118A8/118B	R1W	10	1182	283	540	3555	160	1320	-	41
320/85 R28	(12.4R28)		TL	124A8/124B	R1W	11	1258	321	575	3776	160	1600	-	43
340/85 R28	(13.6R28)		TL	127A8/127B	R1W	12	1308	353	598	3921	160	1750	-	45
380/85 R28	(14.9R28)		TL	133A8/133B	R1W	13	1378	386	627	4124	160	2060	-	47
420/85 R28	(16.9R28)		TL	139A8/139B	R1W	15	1438	439	637	4298	160	2430	-	48
380/85 R30	(14.9R30)		TL	135A8/135B	R1W	13	1407	388	639	4218	160	2180	-	47
420/85 R30	(16.9R30)		TL	140A8/140B	R1W	15	1483	439	674	4440	160	2500	-	48
460/85 R30	(18.4R30)		TL	145A8/145B	R1W	16	1527	466	680	4566	160	2900	-	50
320/85 R32	(12.4R32)	GEN	TL	126A8/126B	R1	11	1357	325	625	4017	160	1700	-	36
380/85 R34	(14.9R34)		TL	137A8/137B	R1W	12	1487	389	681	4470	160	2300	-	47
420/85 R34	(16.9R34)		TL	142A8/142B	R1W	15	1594	439	710	4784	160	2650	-	48
460/85 R34	(18.4R34)		TL	157A8/157B	R1W	16	1649	470	743	4944	160	3075	-	50
320/85 R36	(12.4R36)	GEN	TL	128A8/128B	R1	11	1458	325	672	4316	160	1800	-	36
340/85 R36	(13.6R36)	GEN	TL	132A8/132B	R1	11	1495	345	689	4425	160	2000	-	37
340/85 R38	(13.6R38)	GEN	TL	133A8/133B	R1	12	1543	345	714	4567	160	2060	-	37
420/85 R38	(16.9R38)		TL	144A8/144B	R1W	15	1667	439	752	5014	160	2800	-	48
460/85 R38	(18.4R38)		TL	149A8/149B	R1W	16	1737	470	776	5207	160	3250	-	50
520/85 R38	(20.8R38)		TL	155A8/155B	R1W	18	1863	530	841	5589	160	3875	-	51
650/85 R38			TL	176A8/173D	R1W	20	2072	666	935	6192	240	7100	6500	60
460/85 R42	(18.4R42)		TL	151A8/151B	R1W	16	1865	473	844	5611	160	3450	-	50
520/85 R42	(20.8R42)		TL	162A8/162B	R1W	18	1958	530	875	5884	240	4750	-	51
480/80 R46	(18.4R46)		TL	158A8/158B	R1W	16	1971	490	905	5936	240	4250	-	50
520/85 R46	(20.8R46)		TL	158A8/158B	R1W	18	2062	535	921	6205	160	4250	-	51