

TRACTOR RADIAL

R1/R1W Harvester | Harvester | Pattern R1/R1W



- robust and stable tyre with excellent price-performance ratio
- high tyre volume and load capacities at low inflation pressure
- an aggressive R1-W tread pattern, featuring sharp shoulders for excellent grip
- high traction capabilities and minimum slippage guarantee constant travel speed necessary for proper harvesting operations
- special reinforced belt construction and stubble guard
- extended tyre lifetime due to special tread rubber compound

TRACTOR RADIAL

R1 Defender | Defender (Row Crop) | Pattern R1



- row crop tyres with rounded shoulders for every kind of cultivation, harvesting and spraying operation
- minimum damage to crops even in narrow spaced plantations
- strong radial casing for optimum ground pressure distribution and low ground compaction lowers damage to soil and increases crop yield

TRACTOR RADIAL

R1/R1W Harvester

tyre size		TT/TL	load/speed index	pat-tern tra	measu-red rim width	unloaded		static loaded radius	rolling circum-ference	infla-tion pres-sure	load	tread depth
						outer diameter	section width					
						inch	mm					
620/75 R26	(23.1R26)	TL	166A8/166B	R1	DW20	1605	641	722	4778	320	5300	45
750/65 R26	(28LR26)	TL	166A8/166B	R1	DW25	1600	761	710	4761	240	5300	46
650/75 R32	(24.5R32)	TL	172A8/172B	R1	DW20	1796	658	810	5362	320	6300	48
800/65 R32	(30.5LR32)	TL	172A8/172B	R1W	DW27	1833	797	820	5460	240	6300	57
			178A8/178B							320	7500	

TRACTOR RADIAL

R1 Defender

tyre size	TT/TL	load/speed index	pat-tern tra	measu-red rim width	unloaded		static loaded radius	rolling circum-ference	infla-tion pres-sure	load	tread depth
					outer diameter	section width					
					inch	mm					
230/95 R32	TL	128A8/128B	R-1	8	1240	236	585	3742	400	1800	33
270/95 R32	TL	136A8/136B	R-1	9	1319	284	620	3975	400	2240	35
230/95 R36	TL	130A8/130B	R-1	7	1345	229	626	4063	400	1900	33
270/95 R36	TL	139A8/139B	R-1	9	1422	283	663	4291	400	2430	35
270/95 R38	TL	140A8/140B	R-1	9	1474	285	691	4450	400	2500	35
230/95 R42	TL	133A8/133B	R-1	8	1497	228	684	4527	400	2060	33
270/95 R42	TL	140A8/140B	R-1	9	1580	283	744	4774	360	2500	35
320/80 R42	TL	141A8/141B	R-1	10	1567	315	730	4771	320	2575	35
230/95 R44	TL	134A8/134B	R-1	8	1547	220	735	4679	400	2120	33
270/95 R44	TL	142A8/142B	R-1	8	1632	265	761	4896	400	2650	34
300/95 R46	TL	148A8/148B	R-1	9	1717	305	805	5189	400	3150	36
320/90 R46	TL	148A8/148B	R-1	10	1737	315	810	5248	360	3150	37
340/85 R46	TL	150A8/150B	R-1	11	1770	352	835	5345	360	3350	44
420/80 R46	TL	151A8/151B	R-1	13	1848	398	849	5272	240	3450	45
230/95 R48	TL	136A8/136B	R-1	8	1647	230	780	4984	400	2240	33
270/95 R48	TL	144A8/144B	R-1	9	1734	286	821	5243	400	2800	35
320/90 R50	TL	150A8/150B	R-1	10	1846	319	861	5540	360	3350	42
300/95 R52	TL	151A8/151B	R-1	10	1872	306	903	5527	400	3450	36