

TRACTOR RADIAL

R1W 70+75 | Standard Tyres 70+75 Series | Pattern R1W



- guaranteed true running and driving comfort up to 50 km/h
- wide contact area for up to 4000 working hours
- more and wider lugs in ground and extended wear compound for durability
- excellent driving on and off-the-road
- good self-cleaning abilities due to special angle lugs
- round shoulders for superior ground protection



TRACTOR RADIAL

R1 Genesis 70 | Genesis Tyres 70 Series | Pattern R1



- modern agricultural radial tyre
- the shape and angle of the lugs provide good traction and low slippage with excellent power transmission to the ground
- wide footprint area for improved stability and minimum ground pressure
- superior self-cleaning features that allow for a quick change from field operations to road usage
- low wear compound for longer tyre life



TRACTOR RADIAL

R1W 70+75 | R1 Genesis 70

tyre size	version	TT/TL	load/speed index	pattern	measured rim width	unloaded		static loaded radius	rolling circumference	inflation pressure	load	Tread depth
						outer diameter	section width					
						inch	mm				mm	mm±2.5%
280/70R16	GEN	TL	112A8/112B	R1	9	787	273	357	2350	240	1120	32
280/70 R18	GEN	TL	114A8/114B	R1	9	849	273	385	2542	240	1180	32
360/70 R24		TL	122A8/122B	R1W	11	1135	354	518	3398	160	1500	42
380/70 R24		TL	125A8/125B	R1W	12	1198	384	533	3574	160	1650	42
420/70 R24		TL	130A8/130B	R1W	13	1231	426	563	3675	160	1900	45
480/70 R24		TL	138A8/138B	R1W	15	1314	488	580	3913	160	2360	47
360/70 R28		TL	125A8/125B	R1W	11	1258	356	566	3777	160	920	42
380/70 R28		TL	127A8/127B	R1W	12	1304	382	589	3903	160	1750	42
420/70 R28		TL	133A8/133B	R1W	13	1350	414	597	4044	160	2060	45
480/70 R28		TL	140A8/140B	R1W	15	1431	477	643	4279	160	2500	47
420/70 R30		TL	134A8/134B	R1W	13	1384	422	615	4153	160	2120	45
480/70 R30		TL	141A8/141B	R1W	15	1463	480	653	4382	160	2575	47
520/70 R30		TL	145A8/145B	R1W	16	1528	522	692	4572	160	2900	48
600/70 R30		TL	152A8/152B	R1W	20	1610	586	716	4804	160	3550	51
480/70 R34		TL	143A8/143B	R1W	15	1571	487	720	4717	160	2725	47
520/70 R34		TL	148A8/148B	R1W	16	1639	530	739	4916	160	3150	48
480/70 R38		TL	145A8/145B	R1W	15	1683	483	763	5062	160	2900	47
520/70 R38		TL	150A8/150B	R1W	16	1743	529	787	5238	160	3350	48
580/70 R38		TL	155A8/155B	R1W	18	1822	580	811	5465	160	3875	51
710/70 R38		TL	166A8/166B	R1W	23	1950	741	863	5837	160	5300	58
620/70 R42		TL	160A8/160B	R1W	20	1917	626	841	5762	160	4500	52
710/70 R42		TL	173A8/173B	R1W	23	2079	743	937	6234	240	6500	58
710/75 R42		TL	175D/172E	R1W	23	2127	728	961	6356	240	7245	62