

FLOTATION RADIAL

Agro Grip | Implement Low Pressure Tyres | Pattern Agro Grip



- high load capacity
- 65 km/h approval
- excellent self-cleaning properties for safe driving on and off-the-road
- low ground compaction
- specially suitable for transport on paved roads
- low rolling resistance for fuel saving and comfortable ride
- extended wear compound for enhanced tyre lifetime

Please use only tyres with steel belts for construction machinery.

FLOTATION RADIAL

F1 Traction | Implement Low Pressure Tyres | Pattern F1 Traction



- high load capacity
- 65 km/h approval
- good self-cleaning properties
- suitable for grassland
- low ground compaction
- low rolling resistance
- suitable for on/off-the-road agricultural service on tractors, trailers and agricultural implements

FLOTATION RADIAL

Agro Grip

tyre size		TT/TL	load/speed index	measu - red rim width	unloaded		static loaded radius	rolling circum - ference	infla - tion pres - sure	load	tread depth	
					outer diameter	section width						
					inch	mm						mm
500/60 R22.5		IMP	TL	155D	16	1170	506	528	3509	400	3875	25
560/45 R22.5		IMP	TL	152D	16	1072	538	480	3220	400	3550	25
560/60 R22.5		IMP	TL	161D	16	1256	562	559	3767	400	4625	25
HD 560/60 R22.5	STEEL	IMP	TL	164D	16	1256	562	559	3767	400	5000	25
600/50 R22.5		IMP	TL	159D	20	1168	608	522	3507	400	4375	25
600/55 R22.5		IMP	TL	162D	20	1214	610	537	3643	400	4750	25
650/50 R22.5		IMP	TL	163D	20	1208	654	532	3619	400	4875	25
710/45 R22.5 *		IMP	TL	165D	24	1189	710	530	3567	400	5150	25
600/55 R26.5		IMP	TL	165D	20	1320	610	586	3966	400	5150	25
620/55 R26.5		IMP	TL	166D	20	1378	641	618	4142	400	5300	25
650/55 R26.5		IMP	TL	169D	20	1396	650	625	4196	400	5800	25
HD 650/55 R26.5	STEEL	IMP	TL	178D	24	1396	650	625	4196	500	7500	25
710/50 R26.5	STEEL	IMP	TL	170D	24	1368	728	613	4113	400	6000	25
750/45 R26.5		IMP	TL	170D	24	1345	751	594	4044	400	6000	25
600/60 R30.5	STEEL	IMP	TL	173D	20	1478	624	673	4477	400	6500	25
750/60 R30.5	STEEL	IMP	TL	181D	24	1658	767	735	4986	400	8250	25
850/50 R30.5	STEEL	IMP	TL	182D	28	1652	882	719	4925	400	8500	25

HD = heavy duty * in preparation

FLOTATION RADIAL

F1 Traction

tyre size		TT/TL	load/speed index	measu - red rim width	unloaded		static loaded radius	rolling circum - ference	infla - tion pres - sure	load	tread depth	
					outer diameter	section width						
					inch	mm						mm
500/60 R22.5		IMP	TL	155D	16	1186	483	537	3558	400	3875	26
560/45 R22.5		IMP	TL	152D	16	1085	523	486	3266	400	3550	25
560/60 R22.5		IMP	TL	161D	16	1277	522	570	3837	400	4625	20
600/50 R22.5		IMP	TL	159D	20	1185	580	536	3556	400	4375	26
710/45 R22.5		IMP	TL	165D	24	1189	678	530	3567	400	5150	26
600/55 R26.5		IMP	TL	165D	20	1361	587	608	4046	400	5150	26
710/50 R26.5		IMP	TL	170D	24	1342	678	596	4034	400	6000	26