

IMPLEMENT RADIAL

F1 Traction | Implement Tyres | Pattern F1 Traction



- high load capacity
- 65 km/h approval
- good self-cleaning properties
- suitable for grassland
- low ground compaction
- low rolling resistance
- suitable for on/off-the-road agricultural service on tractors, trailers and agricultural implements

IMPLEMENT RADIAL

R305 | Implement Tyres | Pattern R305



- wide contact area for even ground pressure distribution at low inflation pressure.
- 65 km/h approval
- superior ground protection on grassland and other surfaces
- well balanced pattern design for a great variety of applications
- suitable for municipality vehicles
- excellent drive comfort even on long distances

IMPLEMENT RADIAL

F1 Traction

tyre size	TT/TL	load/speed index	measured rim width	unloaded		static loaded radius	rolling circumference	load		inflation pressure	tread depth
				outer diameter	section width			40 km/h	65 km/h		
				inch	mm			mm	mm±2.5%		
500/50R17 IMP	TL	132A8	16	925	497	412	2780	2000	-	240	15
500/50R17 IMP	TL	145D	16	925	497	412	2780	3940	2900	400	15

IMPLEMENT RADIAL

R305 agricultural machinery, agricultural trailers

tyre size	TT/TL	load/speed index	measured rim width	unloaded		static loaded radius	rolling circumference	variation	load		inflation pressure	tread depth
				outer diameter	section width				40 km/h	65 km/h		
				inch	mm				mm	mm±2.5%		
500/50 R17	TL	157A8/146D	16	927	500	406	2793	LLV*	3450	2500	280	10
								HLV**	4125	3000	380	

*LLV: low load variation

**HLV: high load variation